





Please Approve this Drawing

Date

Signature

NO.	Part Name	Q'TY	Material	Plated surface
1	Plunger	5	HBI59	AU 16U" MIN OVER 56~120 U" NI
2	Barrel	5	HBI59	AU 4U" MIN OVER 56~120 U" NI
3	Spring	5	SUS	N/A
4	Housing	1	High temp.Plastic; UL94 V=0	Color Black



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 36 V ; 1.0A Max.
 - .Contact Resistance: 50 mohm maximum at Working Height(Quiescence)
- Mechanical
 - .Full store: 2.20 mm
 - .Working Store: 2.00 mm
 - .Spring Force: 85gf±25gf at Working Height
 - .Durability:10,000 cycles(minimum)
- Environmental
 - .Operating Temperature: -40°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 48 Hours
- When the current is greater than 1A then need to increase the time delay circuit(3 second)
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage, please operate it based on the working height.
- .RoHs&HF compliant product.

DRAWN	LX	DATE	2021.11.25				Dongguan Promax Electronics Technology Co., Ltd	
CHECKED		SCALE	10:1	VER.	A.0			
APPROVED		TITLE	pogo pin connector.			Ang:	Dim:	
PROJECT		DRAWING NO.	NC4158-05RA			0 ±1°	0 ±0.20	
SHEET	1 of 1	UNIT	mm			.0 ±0.5°	.0 ±0.15	
						.00 ±0.25°	.00 ±0.10	

VER.	DESCRIPTION	ECN NO.	DATE