


Please Approve this Drawing

Date



Signature

NO.	Part Name	Q'TY	Material	Plated surface
1	Plunger	1	HBI59	AU 5 U" MIN OVER 50~120 U" NI
2	Barrel	1	HBI59	AU 3 U" MIN OVER 50~120 U" NI
3	Spring	1	SUS 304	/
4				



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 12 V ; 1.0A
 - .Contact Resistance: 100 mohm maximum at Working Height(Quiescence)
- Mechanical
 - .Full store: 1.20 mm
 - .Working Store: 1.00 mm
 - .Spring Force: 40gf±20%gf at Working Height
 - .Durability:10,000 cycles(minimum)
- Environmental
 - .Humidity Range: 10%RH~90%RH
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage, please operate it based on the working height.
- .RoHS&HF compliant product.

DRAWN	ZYH	DATE	2022.07.27			 Dongguan Promax Electronics Technology Co., Ltd
CHECKED		SCALE	10:1	VER.	A.0	
APPROVED		TITLE	pogo pin			Ang:
PROJECT		DRAWING NO.	NC4963-01PA			0 ±1°
SHEET	1 of 1	UNIT	mm			.0 ±0.5°
						.00 ±0.25°
						Dim: 0 ±0.15
						.0 ±0.10
						.00 ±0.05

VER.	DESCRIPTION	ECN NO.	DATE